

**Agip 7004
SAE 5W-40**

**ACEA A3/B3, A3/B4, C3
VW 502 00
VW 505.00 + 505.01**

Synthetic high performance engine oil for VW vehicles with pump-nozzle-injection, but also for conventional gasoline and diesel engines in passenger cars and van-type trucks.

Characteristics (typical figures):

Agip 7004	Unit	SAE 5W-40	Test Methode
Omschrijving	Unit	Resultaat	Test Methode
Kinematic Viscosity at 40 C	cSt	89	ASTM D 445
Kinematic Viscosity at 100 C	cSt	14	ASTM D 445
Density at 15 C	kg/l	0.855	ASTM D 4052
Flashpoint	C	215	ASTM D 92
Pourpoint	C	-27	ASTM D 97

Properties and Performance:

Synthetic fuel efficiency engine oil of the newest technology that meets the special requirements of engines with pump-nozzle-injection and also can be used in gasoline and diesel engines of the conventional type.

- affords an excellent wear protection due to its synthetic components
- builds up a load-bearing lubrication film under all conditions
- excellent flowability at low temperatures (SAE 5W) due to the high natural viscosity index, therefore reduces the cold start wear
- lowest evaporation loss due to the synthetic components with high thermal stability
- the good detergent and dispersing properties keep the engine clean and effectively prevent the formation of sludge

Applications:

Agip 7004 had been developed especially for the new diesel engine generation with pump-nozzle-injection of VW.

Agip 7004 can also be applied for vehicles with other engine types according to the corresponding manufacturer specifications.

Please observe the manufacturer's specifications when selecting products!

Specifications

Agip 7004 meets or exceeds the requirements of the following specifications.

specificatie
ACEA A3/B3, A3/B4, C3
API SM/CF
VW 502.00
VW 505.00 + 505 01
BMW LL 04
PORSCHE

AAVG, juni '04
GEPRINT: dinsdag 9 juni 2009