

**Agip 7008
SAE 5W-30**

VW 504.00 + 507.00

AGIP 7008 is a top quality lubricant specifically formulated to lubricate gasoline or diesel engines of cars of the Volkswagen group, for which a “Longlife” lubricant meeting the VW 504.00 or 507.00 specifications is prescribed.

Characteristics (typical figures):

AGIP 7008	Unit	SAE 5W-30	Test Methode
Viscosity at -30 C	mPa.s	6000	ASTM D 5293
Kinematic Viscosity at 40 C	cSt	72.0	ASTM D 445
Kinematic Viscosity at 100 C	cSt	11.80	ASTM D 445
Viscosity Index		160	ASTM D2270
Density at 15 C	kg/l	0.850	ASTM D 4052
Flashpoint	C	235	ASTM D 92
Pourpoint	C	-45	ASTM D 97

Properties and Performance:

- The product allows to reach the maximum oil drain intervals set by the engine manufacturer.
- AGIP 7008 is free- flowing at cold temperatures, which allows easier startup.
- It's particularly suitable for those vehicles equipped with DPF (diesel particle filter), for which a longer operating life is allowed
- It has high fuel economy characteristics, which turn into reduced fuel consumption and therefore reduced exhaust emissions.

Applications:

The product is also suitable to lubricate gasoline and diesel engines of the Volkswagen group, for which oils meeting the a/m specifications have been admitted as an alternative to others originally specified

Please observe the manufacturer's specifications when selecting products!

Specifications

Agip 7008, meets or exceeds the requirements of the following specifications.

specificatie
VW504.00 + 507.00

AAVG, juni '04
GEPRINT: dinsdag 25 oktober 2005