

## Agip ASP

**Adhesive oils** based on mineral oil with excellent lubrication properties and especially high wetting capacity.

### Characteristics (typical figures):

Agip ASP	Unit	100	150	220	Test method
Kin. Viscosity at 40°C	mm <sup>2</sup> /s	100	140	205	ASTM D 445
Viscosity index		95	95	95	
Density at 15°C	kg/l	0,887	0,890	0,893	ASTM D 1298
Flashpoint o. C.	°C	235	240	245	ASTM D 92
Pourpoint	°C	-21	-18	-18	ASTM D 97
Designation		CGL	CGL	CGL	DIN 51 502
ISO-VG-grade		100	150	220	

### Properties

**Agip ASP** - types contain a special adhesive component that especially contributes to the prevention of dropping or throwing off as a consequence of centrifugal forces or vibrations. The adhesiveness guarantees an exactly measured good lubrication, also under difficult conditions and reduces the oil consumption especially with loss lubrication. These oils have suitable additives that guarantee excellent rust and corrosion protection of the oil moistened parts.

### Application

**Agip ASP** - types are favourably applied where the machine elements that have to be lubricated are subject to strong vibrations or centrifugal forces or where strong pollution of the parts have to be avoided (food, textile, paper and printing industry) and it can be used in central lubricating systems.

**Agip ASP 100** has also proven as chain saw oil.

Please observe the manufacturer's specifications when selecting products.

AAVG, juni '04  
GEPRINT: dinsdag 3 januari 2006