

Agip City 2T

API TC

Agip CITY 2T is a synthetic low smoke lubricant for the newest generation of 2-stroke-engines of e. g. Scooter. It had been formulated with special synthetic components and is suitable for the application in air- and water-cooled engines.

Characteristics (typical figures):

Viscosity at 100°C	mm ² /s	11
Viscosity at 40°C	mm ² /s	94
Viscosity index		115
Pourpoint	°C	-15
Flashpoint	°C	> 61
Density at 15°C	kg/m ³	880

Properties and Performance:

- ⇒ **Agip CITY 2T** minimises the formation of deposits in the combustion chamber, in the area of the piston rings and in the exhaust system, thus the cleanliness of the engine components is ensured. Simultaneously the spark plug bridge formation is reduced.
- ⇒ The low smoke development in the exhaust gas results from the carefully selection of special synthetic base oils.
- ⇒ The product has excellent self-mix properties, which ensure a very fast mixing with unleaded gasoline, but they are also best suitable for the application in engines with oil-injection systems.
- ⇒ **Agip CITY 2T** takes care of excellent protection of the engine from corrosion, rust and wear.

Applications:

However **Agip CITY 2T** had been especially developed for oil-injection systems it also can be used pre-mixed in unleaded gasoline as well.

Please observe the manufacturer's specifications when selecting products!

Specifications

Agip City 2T, meets or exceeds the requirements of the following specifications.

specificatie
API TC
JASO FC

AAVG, juni '04
GEPRINT: woensdag 27 september 2006