

**Agip Extra HTS
SAE 5W-40**

**ACEA A3, B3, B4
API SL/CF
MB 229.3**

Agip Extra HTS is a highest performance engine oil of the latest generation that meets the requirements of the modern passenger car engines. It is especially formulated for high performance engines and thus best suitable for vehicles operating under high working temperatures and severe conditions.

Characteristics (typical figures):

Agip EXTRA HTS	Unit	SAE 5W-40	Test Methode
Viscosity at -30 C	mPa.s	6500	ASTM D 5293
Kinematic Viscosity at 40 C	cSt	85	ASTM D 445
Kinematic Viscosity at 100 C	cSt	15.1	ASTM D 445
Viscosity Index		176	ASTM D2270
Density at 15 C	kg/l	0.875	ASTM D 4052
Flashpoint	C	200	ASTM D 92
Pourpoint	C	-39	ASTM D 97

Properties and Performance:

- Special synthetic base oils and additives of a new technology ensure ideal viscosity under a wide range of working conditions.
- Due to its viscosity grade **Agip EXTRA HTS** guarantees a fast oil circulation in all moving parts at the engine start independent of external temperatures, even under extreme conditions. This product allows a safe lubrication during cold start with extremely low temperatures as well as during operation with high temperatures.
- The presence of low-volatility components with high thermal stability reduces the oil determined oil consumption.
- The lubricant forms an oily film which adheres tenaciously to metal surfaces even when the engine has been standing for some time, thus ensuring an easy start and reduced wear even under high load conditions.
- The lubricant maintains its viscosity and lubricity even under severe driving conditions. With its unique anti-wear properties a long life for all moving parts is ensured that reduces the need for engine servicing and overhauls.
- Both road and laboratory tests show that this lubricant provides the ideal combination of viscosity, lubricity, volatility and detergency to ensure a maximum protection of the engine, while friction and oil loss are kept to a minimum.
- **Agip EXTRA HTS** is compatible with exhaust catalytic devices and all sealing materials conventionally used in the automotive field. It can also be mixed with all lubricants, which comply with the international automotive specifications.
- **Agip EXTRA HTS** is recycable and like all oils when changed always has to be delivered to an authorised collector for reprocessing.

Please observe the manufacturer's specifications when selecting products!

Specifications

Agip EXTRA HTS meets or exceeds the requirements of the following specifications.

specificatie
ACEA A3/B3, A3/B4
API SL/CF (DONUT)
BMW LONGLIFE 98
GM-LL-B-025
MB 229.3
PORSCHE
VW 502.00 + 505.00

AAVG, juni '04
GEPRINT: maandag 13 juli 2009