

## Agip Forest

**Adhesive oils** based on mineral oil with excellent lubrication properties and especially high wetting capacity.

### Characteristics (typical figures):

Agip FOREST	Unit		Test method
Kin. Viscosity at 40 °C	mm <sup>2</sup> /s	105	ASTM D 445
Viscosity index		100	
Density at 15 °C	kg/l	0,885	ASTM D 1298
Flashpoint o. C.	°C	240	ASTM D 92
Pourpoint	°C	-14	ASTM D 97

### Properties

**Agip FOREST** types contain a special adhesive component that especially contributes to the prevention of dropping or throwing off as a consequence of centrifugal forces or vibrations. The adhesiveness guarantees an exactly measured good lubrication, also under difficult conditions and reduces the oil consumption especially with loss lubrication. These oils have suitable additives that guarantee excellent rust and corrosion protection of the oil moistened parts.

### Application

**Agip FOREST** - types are favourably applied where the machine elements that have to be lubricated are subject to strong vibrations or centrifugal forces or where strong pollution of the parts have to be avoided (food, textile, paper and printing industry) and it can be used in central lubricating systems.

**Agip FOREST** has also proven as chain saw oil.

Please observe the manufacturer's specifications when selecting products.

AAVG, juni '04  
GEPRINT: donderdag 3 december 2009