

Agip FORMULA FUTURE SAE 5W-30

ACEA A3, B4
ACEA C3
MB Approval 229.51
VW 504 00 and 507 00
BMW LL 04

High-Tech engine oil in mid SAPS quality for modern passenger car gasoline and diesel engines with and without DPF also at prolonged oil-change intervals.

Characteristics (typical figures):

| Agip FORMULA FUTURE | Unit | SAE 5W-30 | Test Methode |
|------------------------------|------|-----------|--------------|
| Kinematic Viscosity at 40 C | cSt | 764 | DIN 51 562 |
| Kinematic Viscosity at 100 C | cSt | 12 | |
| Viscosity Index | | 161 | DIN ISO 2909 |
| Density at 15 C | kg/l | 0.850 | DIN 51 757 |
| Flashpoint | C | >200 | DIN ISO 2592 |
| Pourpoint | C | -42 | DIN ISO 3016 |

Properties and Performance:

Agip FORMULA FUTURE is a synthetic High-Tec engine oil of the newest generation. Next to the general requirements of the ACEA it also meets the requirements for vehicles with exhaust gas aftertreatment systems and turbo charger. Additionally the current requirements of Mercedes-Bens, BMW, Renault and Volkswagen are met. A backwards compatibility is given according to the manufacturer's recommendations.

Agip Formula FUTURE excels through:

- Excellent wear protection
- Universal application
- Optimum cold start properties
- Proven fuel saving
- Low oil consumption
- Gentle treatment of the catalysts through low phosphorus content
- Meets the requirements concerning DPF (mid SAPS)

Applications:

Agip FORMULA FUTURE is a multiple applicable oil. Due to its broad performance among other applications at following regulations are possible: ACEA C2; C3-03, ACEA A3/B4; MB Approval 229.3 and 229.5 as well as 229.31 and 229.51; BMW Longlife-oil (01, 01 FE, 04) and as VW Longlife II (503 00, 506 00, 506 010 and Longlife III (504 00, 507 00) as well as VW/Audi 503 01, Renault C3-04.

Pls observe the manufacturer's specifications when selecting products.

CvO mar-09
GEPRINT: donderdag 19 maart 2009