

Agip Formula LL G SAE 5W-30

**ACEA A3/B3/B4
GM-LL-A-025
GM-LL-B-025**

High-performance oil in Longlife quality with proven fuel saving due to the SAE 5W-30 for all Opel gasoline and diesel engines, also for Opel diesel vehicles with diesel particle filter (DPF).

Characteristics (typical figures)

Agip FORMULA LL G	Unit	SAE 5W-30	Test Methode
Kinematic Viscosity at 40 C	cSt	70.5	ASTM D 445
Kinematic Viscosity at 100 C	cSt	11.8	ASTM D 445
Viscosity Index		165	ASTM D2270
Density at 15 C	kg/l	0.855	ASTM D 4052
Flashpoint	C	234	ASTM D 92
Pourpoint	C	-42	ASTM D 97

Properties and Performance

- **Agip FORMULA LL G** is an unconventional high performance engine oil of the newest technology with proven fuel saving properties.
- Under all driving condition it has a high lubrication film strength.
- The high wear protection ensures a long engine life.
- The modern technology reduces the emissions and therefore relief the environment.
- Approved for Opel vehicles with DPF.
- Approved for Opel vehicles with ECOService-Flex.
- Oil change intervals up to 30.000 km or max. 2 years for gasoline engines
up to 50.000 km or max. 2 years for diesel engines

Applications

Agip FORMULA LL G is a modern Longlife oil with fuel saving properties, especially for the new gasoline and diesel engines of Opel, but also for older vehicles without ECOService-Flex. It is also applicable for Opel diesel vehicles with diesel particle filter (DPF). Furthermore it is suitable for other vehicle types with the manufacturer specification ACEA A3/B3/B4.

Before the application of **Agip FORMULA LL G** in other makes the manufacturers specifications, especially the ACEA, have to be checked.

SPECIFICATIES

Agip FORMULA LL G meets or exceeds the requirements of the following specifications:

specificatie
ACEA A3, B3
API SL/CF
GM-LL-A-025
GM-LL-B-025

AAVG, juni '04
GEPRINT: maandag 6 juni 2005