

Agip Speed 2T

API TC

Agip Speed 2T is a fully synthetic two-stroke oil for extremely loaded 2-stroke engines of Motorbikes that are used in the normal traffic and in racing sports.

Characteristics (typical figures):

SAE		40
Viscosity at 100°C	mm ² /s	12,6
Viscosity at 40°C	mm ² /s	95
Viscosity index		137
Pourpoint	°C	-42
Flashpoint o. C.	°C	80
Density at 15°C	kg/m ³	915

Properties and Performance:

- ⇒ **Agip Speed 2T** has been developed with a very modern synthetic base oil, which ensures excellent engine performance also at highest temperatures. It guarantees highest cleanliness of all engine parts and excellent wear protection.
- ⇒ The product has excellent detergent properties that reduce the formation of sludge and deposits at all engine parts and protect from ring sticking.
- ⇒ It had been formulated with selected synthetic base oils and a special additive package, to achieve this excellent performance.

Applications:

Agip Speed 2T is suitable for oil-in-gasoline lubrication and separate lubrication (oil-injection). It can be used in unleaded fuel.

Please observe the manufacturer's specifications when selecting products!

Specifications

Agip Speed 2T, meets or exceeds the requirements of the following specifications.

specificatie
API TC
ISO-L-EGD
JASO FC

AAVG, juni '04
GEPRINT: woensdag 27 september 2006