

Agip Super 4T SAE 15W-50

ACEA A3-98
JASO MA

AGIP SUPER 4T SAE 15W-50 is a multigrade mineral oil of the latest technology for 4 stroke bike engines. It satisfies the demand of engines under the most severe and varied operating conditions.

Characteristics (typical figures):

SAE GRADE		15W-50
Viscosity at 100°C	mm ² /s	17.7
Viscosity at 40°C	mm ² /s	128
Viscosity at -15°C	mPa's	3000
Viscosity Index		148
Pour Point	°C	-27
Flash Point COC	°C	230
Mass density at 15/15°C	kg/l	0.882

Properties and Performance:

Ensures perfect lubrication

- Minimizes the formation of lacquer and varnish, as well as other deposits.
- Prevents ring sticking, keeps pistons clean and maintains deposits in suspension.
- Resistant to deterioration especially that caused by prolonged high-temperature operation.

Applications:

AGIP SUPER 4T SAE 40 is single grade mineral oil of medium performance level suitable for those 4T bike engines not of the latest technology and/ or not particularly demanding in terms of lubrication. It offers a valid alternative should an optimized cost / performance ratio is sought rather than maximum performance.

Please observe the manufacturer's specifications when selecting products!

Specifications

Agip Super 4T, meets or exceeds the requirements of the following specifications.

specificatie
ACEA A3-98
API SJ (DONUT)
JASO MA

AAVG, juni '04
GEPRINT: woensdag 27 september 2006