

**Agip Tec sint
SAE 5W-30**

**API SL/CF
ACEA A3/B3/B4
MB 229.3**

High-tech fuel efficiency engine oil of the Agip technology with proven fuel economy in modern passenger car engines.

Characteristics (typical figures):

Agip TECSINT	Unit	SAE 5W-30	Test Methode
Kinematic Viscosity at -20 C	cP	3050	DIN 51561
Kinematic Viscosity at 40 C	cSt	64.5	ASTM D 445
Kinematic Viscosity at 100 C	cSt	11.8	ASTM D 445
Viscosity Index		173	ASTM D2270
Density at 15 C	kg/l	0.880	ASTM D 4052
Flashpoint	C	225	ASTM D 92
Pourpoint	C	-42	ASTM D 97

Properties and Performance:

Agip TECSINT is a modern high-tech engine oil that already meets the future requirements for engine oil concerning the fuel efficiency and pollutant emission reduction.

Especially selected fully synthetic base oils and carefully co-ordinated additives ensure a safe lubrication of the engine under all conditions, connected with a reduction of the friction at proved reduction of the fuel consumption.

The classification in the new ENERGY CONSERVING (EC) for the API grade SJ is based on a proved reduction of the fuel consumption of 3%.

Agip TECSINT also meets the enhanced requirements of the catalytic converter suitability. Further characteristics are

- the low evaporation tendency
- excellent low temperature behaviour and
- very good shear stability in the high temperature range

The reliable Agip formulation ensures excellent high and low temperature properties that are the requirements for a minimisation of the feared cold start wear but also for a stable lubrication film in the high temperature area.

Agip Benelux B.V.

Eemhavenweg 50
3089 KH Rotterdam

Tel: 010 – 2941555 – Fax: 010 – 4294594

www.agip.nl

Applications:

Agip TECSINT is a high-quality turbo-tested fuel economy efficiency oil for all modern passenger car engines with multi-valve technique, variable valve adjustment, turbo charger or Intercooler.

Agip TECSINT is approved by well-known vehicle manufacturers for the longest oil change intervals according to manufacturer specifications.

Due to the fuel saving viscosity 5W-30 in connection with the modern additive package the requirements of the vehicle manufacturers for classic engine oils are met, which is also documented by the approvals by name.

Please observe the manufacturer's specifications when selecting products!

Specifications

Agip TECSINT, meets or exceeds the requirements of the following specifications.

specificatie
ACEA A3/B3/B4
API SL/CF (donut)
BMW LONGLIFE-98
GM-LL-B-025
MB 229.3
VW 502.00 + 505.00

AAVG, juni '04
GEPRINT: dinsdag 25 oktober 2005