

**Agip Tec sint SX  
SAE 0W-40**

**ACEA A3/B3/B4  
API SL/CF  
MB 229.3**

**Fully synthetic high-tech fuel efficiency oil** of the Agip technology with the SAE 0W-40 with indicated fuel economy in modern passenger car engines.

## Characteristics (typical figures):

Agip TECSINT SX	Unit	SAE 0W-40	Test Methode
Viscosity at -35 C	mPa.s	6600	ASTM D 5293
Kinematic Viscosity at 40 C	cSt	78.0	ASTM D 445
Kinematic Viscosity at 100 C	cSt	14.0	ASTM D 445
Viscosity Index		182	ASTM D2270
Density at 15 C	kg/l	0.860	ASTM D 4052
Flashpoint	C	216	ASTM D 92
Pourpoint	C	-42	ASTM D 97

## Properties and Performance:

**Agip TECSINT SX** is a modern high-tech engine oil, which meets already today the requirements for the future in reference to fuel economy, reduction of emission rate and protection of the environment. Specially chosen fully synthetic base oils, the ester component and carefully adjusted additives ensure a safe lubrication of the engine under all circumstances, combined with wear reduction, indicated fuel economy and less pollutant emission. Also the new requirements of the ACEA B4-98 for DI-diesel engines are met by this high-tech engine oil **Agip TECSINT SX**, SAE 0W-40.

**Agip TECSINT SX** also meets the enhanced requirements of the catalytic converter suitability due to limited phosphorus content. Additional characteristics are lowest vaporisation tendency, very good low temperature behaviour and very good shear stability at high temperatures. The proved Agip ester-technology ensures excellent high and low temperature qualities, which are the requirements for a minimisation of the dreaded cold start wear, but also for a stable lubricating film at high temperatures.

## Applications:

**Agip TECSINT SX** is a high quality, turbocharger tested fuel economy oil for all modern passenger car engines with multi-valve technique, variable valve adjustment, turbocharger or intercooler. **Without prolonged oil-change-intervals** (WIV) it also can be used in the newest VW-vehicles starting model year 2000.

All renowned vehicle manufacturers except of VW, approve AGIP TECSINT SX for prolonged oil-change-intervals.

Please observe the manufacturer's specifications when selecting products!

## Specifications

**Agip TECSINT SX**, meets or exceeds the requirements of the following specifications.

specificatie  
ACEA A3/B3/B4  
API SL/CF (donut)  
MB 229.3  
PORSCHE  
VW 502.00 + 505.00

AAVG, juni '04  
GEPRINT: dinsdag 25 oktober 2005