

**Agip Universal Multifleet
SAE 15W-40**

**API SL/CF-4
MB 228.1/229.1
ACEA A3-98/B3/B4/E2**

High-performance engine oil for highly loaded diesel and gasoline engines with and without charging for the mixed motor pool and for prolonged oil change intervals according to manufacturer's specification.

Characteristics (typical figures):

Agip UNIVERSAL MULTIFLEET	Unit	SAE 15W-40	Test Methode
Kinematic Viscosity at 40 C	cSt	128	ASTM D 445
Kinematic Viscosity at 100 C	cSt	14.50	ASTM D 445
Viscosity Index		163	ASTM D2270
Density at 15 C	kg/l	0.880	ASTM D 4052
Flashpoint	C	225	ASTM D 92
Pourpoint	C	-24	ASTM D 97

Properties and Performance:

- **Agip UNIVERSAL MULTIFLEET** has a high natural viscosity index and ensures a good viscosity-temperature-behaviour. This VT behaviour guarantees a fast lubrication of the engine at all temperatures and recommends this oil for the all-year application.
- High-quality ageing resistant base oils and the performance reserves of the additive package allow the application for prolonged oil change intervals according to the manufacturer's specification.
- Detergent additives keep the pistons and piston ring grooves clean, prevent coking and pigmenting and make the requirements for the application in gasoline engines with and without catalytic converter as well as in diesel engines with turbo charging at severe engine working conditions.
- Additives against wear and corrosion ensure optimum conditions in all bearings, at cylinder faces and other friction points. Bore-polishing is prevented
- **Agip UNIVERSAL MULTIFLEET** is compatible with all common ring and flat sealings used in the engine manufacturing. The miscibility with other brand engine oils that correspond with the national and international standards and specifications is ensured.

Applications:

Agip UNIVERSAL MULTIFLEET has a higher performance reserve than engine oils of the performance class API CD/CE and therefore is called an SHPD-oil.

Agip UNIVERSAL MULTIFLEET has multigrade character and therefore can be used as all-year oil for thermally and mechanically highly loaded diesel and gasoline engines. Just in the mixed motor pool the use of the Agip UNIVERSAL MULTIFLEET causes a rationalisation by a reduction of the oil qualities and prevents mistakes.

Please observe the manufacturer's specifications when selecting products!

Specifications

Agip UNIVERSAL MULTIFLEET, meets or exceeds the requirements of the following specifications.

specificatie
ACEA A3-98/B3/B4/E2
API SL/CF-4
MAN 271
MB 228.1
MB 229.1
VW 501.00 + 505.00 (level)

AAVG, juni '04
GEPRINT: dinsdag 25 oktober 2005