

## Greases

### Autol TOP 2000

KP 2 G-30

resistant to salt water  
extremely adhesive

**Super-Longtime-Grease** with a synthetic base oil for longer regreasing intervals

|  |                    |                       |
|--|--------------------|-----------------------|
| Soap Basis                                   |                    | special Ca. soap      |
| Temperature range                            | °C                 | -30 to +110           |
| Drop point                                   | °C                 | 150                   |
| Base oil viscosity at 40°C                   | mm <sup>2</sup> /s | 850                   |
| Behaviour to Water                           |                    | 0-90                  |
| Corrosion protection properties (EMCOR-Test) |                    | Corr. -grade. 0 and 0 |

**Autol TOP 2000** is a special grease with exceptional adhesive properties and very good extreme-pressure-properties - a real Super-Longtime-Grease suitable for very long regreasing intervals.

Under difficult conditions it reduces wear and is especially resistant to wash outs in the lubrication points. It is extremely resistant to salt water, cooling lubricators, plant preservatives and many lyes.

Due to its composition and if applied as directed, according to the manufacturers regulations, it is physiological harmless and therefore also suitable for the application as lubrication in the foodstuff industry.

#### Applications:

**Autol TOP 2000** is a high pressure grease for the lubrication of vehicles, industrial, constructional and agricultural machines. It can be used without problems in critical lubrication points (impact loads, high moisture, salt water, high pressure with low relative movement). It can also be used for industrial robots, continuous transporters as well as for boats or winter service. Despite the high base oil viscosity the application in central lubricating systems is possible without problems.

For the use in wheel and axle bearings we recommend **AUTOL TOP 2000 High Temp.**

**Attention!** The highest short-time peak temperature permitted is +125°C.

Please observe the manufacturer's specifications when selecting products.