



Motoroil 5W-30 Premium Synthetic ***** C3 Longlife 229.51 / LL-04

Product Information: 05000DPF



Article Nr.	Content	PU	Pallet Content
05001DPF	1 Ltr	6	600
05005DPF	5 Ltr	4	160
05020DPF	20 Ltr.	1	30
05060DPF	60 Ltr	1	9
05205DPF	205 Ltr	1	4
P05000DPF	Bulk		

Application

This synthetic top quality Longlife engine oil is specially developed for Euro-4 engines according to the ACE C3 standard. This engine oil is recommended for all gasoline- en diesel engines which are equipped the latest exhaust gas after treatment systems and for fill the performance criteria according to BMW LL-04 and MB-Approval 229.51

Description

MPM Motor oil 5W-30 Premium Synthetic C3 Longlife 229.51 / LL-04 is composed according to the latest technology, based on especially selected base oils, with highly advanced added additives to obtain the following properties:

- Low formation of burned residue (mid SAPS)
- Fuel conservation
- A fast cold start
- Extended oil drain intervals
- A safe lubricating film at high operating temperatures.
- A strong anti-wear, anti-corrosion and anti-foam ability.
- A strong detergency and dispersion power.

Specifications

API SM/CF	ACEA A3/B3, A3/B4, C3
VW 502.00 / 505.00	MB-Approval 229.51 / 229.31
BMW LL-04	

Typicals:

SAE	5W-30		
Density	15 °C	kg/l	0.852
Viscosity CCS	-30°C	mPa.s	5970
Kin. Viscosity	40°C	mm ² /s	74.40
Kin. Viscosity	100°C	mm ² /s	12.20
Viscosity Index			162
Flashpoint, COC		°C	226
Pourpoint		°C	-42
Total Base Number		mgKOH/g	7.5
Sulphated Ash		% massa	0.8