



# Motoroil 10W-40 \*\*\*\* Semi Synthetic SL/CF

Product Information: 04000

| Article Nr. | Content | PU | Pallet Content |
|-------------|---------|----|----------------|
| 04001       | 1 Ltr   | 12 | 480            |
| 04005       | 5 Ltr   | 4  | 128            |
| 04025       | 25 Ltr. | 1  | 24             |
| 04060       | 60 Ltr  | 1  | 12             |
| 04205       | 205 Ltr | 1  | 4              |
| P04000      | Bulk    |    |                |



## Application

MPM Motoroil 10W-40 Semi Synthetic is an universal, fuel conserving motor oil, developed for all petrol- and LPG-engines. This lubricant is extremely suitable for passenger vehicles as well as commercial vehicles, operating under the heaviest circumstances and in all seasons. MPM Semi Synthetic exceeds the demands of prominent automobile manufacturers.

## Description

MPM Motoroil 10W-40 Semi Synthetic is an ultra modern motor oil based on high-quality solvent refined, mineral and synthetic base oils, of which by nature contain a high Viscosity Index. Because of the addition of unique additives, the following properties are obtained:

- A very high Viscosity Index.
- A reduction of fuel consumption.
- A fast cold start, resulting in less wears.
- A strong detergency and dispersion power preventing from deposits in the engine.
- A more improving duration against high temperatures resulting in a good oil-film at high temperatures.
- A strong protection against wear, corrosion and foaming.

## Specification

**API SL/CF**  
**MB 229.1**  
**ACEA A3/B3/B4**  
**VW 500.00 / 505.00**

## Typicals

| SAE               | 10W-40 |                    |       |
|-------------------|--------|--------------------|-------|
| Density           | 15°C   | kg/l               | 0.873 |
| Viscosity CCS     | -40°C  | mPa.s              | 6500  |
| Kin. Viscosity    | 40°C   | mm <sup>2</sup> /s | 100.0 |
| Kin. Viscosity    | 100°C  | mm <sup>2</sup> /s | 14.60 |
| Viscosity index   |        |                    | 151   |
| Flashpoint, COC   |        | °C                 | 224   |
| Pourpoint         |        | °C                 | -27   |
| Total Base Number |        | mgKOH/g            | 7.7   |
| Sulphated Ash     |        | %mass              | 0.9   |