

eni i-Sint tech G 5W-30



eni i-Sint tech G 5W-30 is a high-performance synthetic engine oil primarily intended for use in General Motors (GM) vehicles where a product for extended (LL - Long Life) service intervals, meeting the GM-LL-A025 or the GM-LL-B025, is required.

Characteristics (typical figures)

SAE Grade		5W-30
Viscosity at 100 °C	mm ² /s	11.8
Viscosity at 40 °C	mm ² /s	70
Viscosity at -30 °C	mPa s	6100
Viscosity Index	-	163
Flash Point	°C	210
Pour Point	°C	-33
Mass Density at 15 °C	kg/m ³	0.855

Properties and Performance

- **eni i-Sint tech G 5W-30** offers excellent performance at both very low and very high operating temperatures and long term engine protection from wear and sludge and deposit buildup.
- Permits extended operation at elevated temperatures without oxidative oil thickening and oil breakdown.
- Provides excellent fluidity at low temperatures allowing easy winter starting and rapid oil circulation around the engine.
- Suitable for use in both gasoline and diesel engine passenger car and light commercial vehicles.

Specifications

eni i-Sint tech G 5W-30 meets the requirements of the following service specifications:

- * GM LL-A-025, B-025
- * ACEA A3/B4-04
- * API SL/CF